

# CR 55 4-WAY

## Truck Mounted Forklift

**PALFINGER**



### Increased accessibility

The PALFINGER CR 55 4-WAY Truck Mounted Forklift features the unique center seating position which gives the operator easier on-and-off access, a more stable feel, and much better view for judging load centers or mounting the truck. Transition to 4-way operation is enabled via hydraulic lever while parked. The CR 55 4-WAY has the shortest 4-WAY truck mounted overhang in the industry (57"). Light weight plus a center of gravity moved closer to the truck axle puts less stress on the truck or trailer.



Reliable and efficient

PALFINGER Inc.  
 7942 Dorchester Rd.  
 Niagara Falls, ON L2E 6V6  
 Canada  
 Tel. 905-374-3363  
 Fax 905-374-1203  
 Toll Free 800-567-1554  
 www.palfinger-northamerica.com

CR 55 4W  
 04.12

**CR 55 4-WAY Truck Mounted Forklift**



**Technical Specifications**

Capacity at 24" (600 mm) Load Center	5500 lbs	2500 kg
Lift Height	122" / 146"	3100mm / 3700 mm
Diesel Engine	64 HP	47.8kW
Rated Speed	2800 rpm	2800 u/min
Lighting System for Transport (Truck)	12V	74Ah
Electronic System (Forklift)	12V	74Ah
Driven Wheels	3	
Steering	Hydrostatic	
Max. Speed	7.5 mph	12 km/h
Theoretical Gradability	30%	
Turning Circle Diameter Wall to Wall	80"	2032 mm
Dead weight (Dry Weight, Without Forks)	5654 lbs / 5830 lbs	2570 kg / 2650 kg
Working Pressure	2943 psi	205 bar
Overhang on the Vehicle	57"	1450 mm
Tire Dimension Front	10" x 16.5"	
Tire Dimensions Back	31" x 15.5" x 15"	
Fuel Capacity	10.6 US gal	40 liter



Applications shown in the leaflet do not always correspond to the standard specifications. Design and specification are subject to change without prior notice.

www.palfinger-northamerica.com