


# Container Carriers

**PALFINGER**



We help you work smarter... not harder

American Roll-Offs are engineered to eliminate down time. It's the small details; full flow hydraulics, high strength engineered materials, and hydraulic components that make our products exceptional. Plus every American Roll-Off goes through an extensive check prior to delivery.



# CC 80

Static 8,000 lb. capacity



## STANDARD FEATURES INCLUDE:

- Unitized mounting with heavy duty container forks
- We help you work smarter... not harder

## SPECIFICATIONS:

- |                                  |             |
|----------------------------------|-------------|
| • Lifting capacity               | 8,000 lb.*  |
| • Weight (approx)                | 5,000 lb.   |
| • Forks (heat treated) - bolt on | 4" x 1-1/2" |
| • Control valve - 2 spools       | 20 GPM      |
| • Operating pressure             | 1,650 PSI   |
| • Hydraulic tank                 | 12 GAL      |
| • Lift cylinders                 | 3-1/2"      |
| • Tilt cylinders                 | 4"          |

## RECOMMENDED CHASSIS SPECIFICATIONS

- |                     |                     |
|---------------------|---------------------|
| • Minimum C.A.      | 60"                 |
| • Recommended G.V.W | 16,000 - 24,000 lb. |

\* Nominal lifting and rotating capacity of CC-80 container carrier under normal operating and driving conditions. Containers with load centers beyond the midpoint of the forks will reduce capacity.